

CANCORE CORE IDENTIFICATION GUIDE

‘CN’ – SERPENTINE FIN WITH
5/8” TUBE ON 7/16” PITCH



2 ROW- 1.4375” *5 ROW- 3.8125”
3 ROW- 2.25” *6 ROW- 4.5625”
4 ROW- 3.00” *7 ROW- 5.3125”
 *8 ROW- 6.1875”
 (*TWO PIECE)

‘CL’ – SERPENTINE FIN WITH 5/8”
LOW FLOW TUBE ON 7/16” PITCH



2 ROW- 1.4375” *5 ROW- 3.8125”
3 ROW- 2.25” *6 ROW- 4.5625”
4 ROW- 3.00” *7 ROW- 5.3125”
 *8 ROW- 6.1875”
 (*TWO PIECE)

‘CT’ – SERPENTINE FIN WITH
1/2” TUBE ON 7/16” OR 9/16” PITCH



2 ROW - 1.0625” *6 ROW- 3.875”
3 ROW - 1.613” *7 ROW- 4.3125”
4 ROW - 2.50” (* TWO PIECE)
5 ROW - 3.00”

‘CP’ – SERPENTINE FIN WITH
3/4” TUBE ON 7/16” PITCH
‘CPL’ – LOW FLOW VERSION



2 ROW – 1.625” 5 ROW – 4.25”
3 ROW – 2.50” 6 ROW – 5.125”
4 ROW – 3.375”

‘R’ – LOUVERED FLAT FIN
WITH 1/2" TUBE ON 5/8" PITCH



2 ROW- 1.073” 6 ROW- 3.233”
3 ROW- 1.613” 7 ROW- 3.773”
4 ROW- 2.153” 8 ROW- 4.313”
5 ROW- 2.693”

‘RL’ – LOW FLOW, LOUVERED FLAT
FIN WITH 1/2” TUBE ON 5/8” PITCH




2 ROW- 1.073” 6 ROW- 3.233”
3 ROW- 1.613” 7 ROW- 3.773”
4 ROW- 2.153” 8 ROW- 4.313”
5 ROW- 2.693”

'Q' – DIMPLED FLAT FIN WITH
1/2" TUBE ON 5/8" PITCH



2 ROW- 1.073" 6 ROW- 3.233"
3 ROW- 1.613" 7 ROW- 3.773"
4 ROW- 2.153" 8 ROW- 4.313"
5 ROW- 2.693"

'N' – COPPER OR STEEL PLAIN FLAT
FIN WITH 1/2" TUBE ON 5/8" PITCH




*4 ROW- 2.8125" 7 ROW- 5.0625"
(*COPPER ONLY) 8 ROW- 5.8125"
5 ROW- 3.5625"
6 ROW- 4.3125"

'H' – DIMPLED FLAT FIN WITH
3/4" TUBE ON 7/16" PITCH



3 ROW- 2.50" *7 ROW- 7.00"
4 ROW- 3.375" *8 ROW- 7.25"
5 ROW- 4.25" (*TWO PIECE)
6 ROW- 5.125"

'F' – PLAIN OR LOUVERED FLAT
FIN WITH 1/2" TUBE ON 1/2" PITCH




3 ROW - 2.25"

MAX HEIGHT 30"

CAN BE PLAIN OR
LOUVERED FIN

*** PLEASE SPECIFY WHICH ***

'L' – LOUVERED FLAT FIN
WITH 1/2" TUBE ON 1/2" PITCH




4 ROW- 2.25" 7 ROW- 3.75"
5 ROW- 2.25" 8 ROW- 4.50"
6-3 ROW- 3.75" 11 ROW- 6.00"

CAN HAVE **SMOOTH** (L SPECIAL) OR
DIMPLED TUBES (LL SPECIAL)

NO HEAVY HEADERS

'P' – PLAIN FLAT FIN WITH
1/2" TUBE ON 1/2" PITCH



4 ROW- 2.25" 7 ROW- 3.75"
5 ROW- 2.25" 8 ROW- 4.50"
6-3 ROW- 3.75" 11 ROW- 6.00"

CAN HAVE **SMOOTH** (P SPECIAL) OR
DIMPLED TUBES (PL SPECIAL)

NO HEAVY HEADERS